



Radium
Die Lichtmarke



New
LED Lamps
2020

Just whatever?
That was yesterday.

**The best light
for bright minds.**

www.radium.de/led-lamps

Just whatever? That was yesterday.

The best light for bright minds.

You want the best light for your lighting project? Then do you just take whatever? Certainly not. With the new LED lamp portfolio from Radium, we offer you high-quality products at reasonable conditions. We are thus following the trend that quality, sustainability and responsibility are once again in demand. Moving away from cheap products that are produced under questionable conditions. Towards branded products that are also worth their money.



Broad portfolio with over 200 models

With our new portfolio, we have increased our offering of LED lamps from 80 to over 200. In addition, you now benefit from even better technical specifications. This means that you will find the right LED lamps for every requirement – from the entry-level to the premium segment.



Quality made in Germany

Our RaLEDina, for example, doesn't come from the Far East, but from Wipperfurth. The decorative line lamp replaces the predecessor model Ralina and is manufactured on the same production line. With Radium, you trust a brand that economically combines state-of-the-art lighting technology and a responsible product policy.



Efficient with high-quality materials

The technical development of LED lamps is proceeding rapidly. This can also be seen in our portfolio, which now offers even better performance thanks to extended service life and increased performance. In addition, many models impress with their elegant all-glass design. This also means that most of our lamps do not have a heat sink.



Safety through long guarantee

Thanks to the high quality of our products, we offer up to five years guarantee on the entire portfolio. The differences in duration usually relate to the “Star” and “Essence” product families. Further information on the guarantee conditions can be found at www.radium.de/guarantee.

Contents

LED Classic	04
LED Spots	14
LED Tubes	22
LED Special	34
LED's Save Calculator	44
Technical information	45
Explanation of pictograms	46

**„For us, it's important
to know how the lamps
are manufactured.“**



Irrelevant? That was yesterday.

Sustainable light for people who stop and think.

Sustainability is becoming increasingly important – for private customers as well as for companies and building operators. Radium's new LED lamp portfolio focuses on this topic: with high-quality products in classic design such as the Classic A in bulb shape, the Classic D in drop shape and the Classic C in candle shape. Without fancy gimmicks, but instead in proven Radium brand quality. For people who think before they buy LED lamps.



**„Especially today,
sustainability should
be supported by
purchasing behavior.“**



**LED
Classic**

LED Classic

High-quality lamps in classic design

Proven designs with state-of-the-art technology

- Lamps in classic design
- Cosy warm white light or colder light colors
- Simple 1:1 exchange
- Extremely energy-saving: up to 85 %
- Long service life: up to 15,000 hours
- Instant 100 % light

Areas of application

- Restaurants
- Hotels
- Bars
- Apartments and private homes



LED Star Classic A

d mm

l mm

Pcs.

h



1	43519263	RL-A60 DIM 827/F/E27	7.0	806	60	105	E27		10	A++	15000
1	43518313	RL-A60 DIM 840/F/E27	7.0	806	60	105	E27		10	A++	15000
1	43518314	RL-A75 DIM 827/F/E27	8.5	1055	60	105	E27		10	A++	15000
1	43518315	RL-A75 DIM 840/F/E27	8.5	1055	60	105	E27		10	A++	15000
2	43518316	RL-A100 DIM 827/F/E27	12.0	1521	60	105	E27		10	A++	15000



— 4 —
YEARS
GUARANTEE

W

lm



L70

LED Essence Classic A

d mm

l mm

Pcs.

h



Glass

1	43619183	RL-A40 827/F/E27	4.0	470	60	105	E27	●	10	A++	15000
1	43619184	RL-A40 840/F/E27	4.0	470	60	105	E27	○	10	A++	15000
1	43619185	RL-A60 827/F/E27	6.5	806	60	105	E27	●	10	A++	15000
1	43619186	RL-A60 840/F/E27	6.5	806	60	105	E27	○	10	A++	15000
1	43619187	RL-A75 827/F/E27	7.5	1055	60	105	E27	●	10	A++	15000
1	43619188	RL-A75 840/F/E27	7.5	1055	60	105	E27	○	10	A++	15000
1	43619189	RL-A100 827/F/E27	11.0	1521	60	105	E27	●	10	A++	10000
1	43619556	RL-A100 840/F/E27	11.0	1521	60	105	E27	○	10	A++	15000
2	43619190	RL-A150 827/F/E27	15.0	2500	70	126	E27	●	10	A++	15000
2	43619191	RL-A150 840/F/E27	15.0	2500	70	126	E27	○	10	A++	15000



5
YEARS
GUARANTEE

1

W

lm



L70

LED Star Classic A

d mm

l mm

Pcs.

h



Glass

1	43518312	RL-A60 DIM 827/C/E27 FIL	7.0	806	60	105	E27		10	A++	15000
---	----------	--------------------------	-----	-----	----	-----	-----	--	----	-----	-------



4
YEARS
GUARANTEE

1

2

3

W

lm



L70

LED Essence Classic A

d mm

l mm

Pcs.

h



Glass

1	43019088	RL-A40 827/C/E27 FIL	4.0	470	60	105	E27		10	A++	15000
1	43618711	RL-A40 840/C/E27 FIL	4.0	470	60	105	E27		10	A++	15000
2	42619089	RL-A60 827/C/E27 FIL	6.5	806	60	105	E27		10	A++	15000
2	43618713	RL-A60 840/C/E27 FIL	6.5	806	60	105	E27		10	A++	15000
3	43618714	RL-A75 827/C/E27 FIL	8.0	1055	60	105	E27		10	A++	15000
3	43618715	RL-A75 840/C/E27 FIL	8.0	1055	60	105	E27		10	A++	15000
3	43618716	RL-A100 827/C/E27 FIL	11.0	1521	60	105	E27		10	A++	10000
3	43618717	RL-A100 840/C/E27 FIL	11.0	1521	60	105	E27		10	A++	10000



1

— 5 —
YEARS
GUARANTEE



LED Star Mini-Ball

d mm l mm Pcs. h



1	43519557	RL-D40 DIM 827/F/E14	4.5	470	45	78	E14		10	A++	15000
---	----------	----------------------	-----	-----	----	----	-----	--	----	-----	-------



1



2



3

— 4 —
YEARS
GUARANTEE



LED Essence Mini-Ball

d mm l mm Pcs. h



1	43619254	RL-D40 827/F/E14	4.0	470	45	77	E14		10	A++	15000
1	43619554	RL-D40 840/F/E14	4.0	470	45	77	E14		10	A++	15000
2	43619255	RL-D40 827/F/E27	4.0	470	45	77	E27		10	A++	15000
3	43619256	RL-D60 827/F/E14	6.5	806	45	110	E14		10	A++	15000



- 5 -
YEARS
GUARANTEE

1



LED Star Mini-Ball

d mm l mm Pcs. h



1	43519265	RL-D40 DIM 827/C/E14 FIL	4.5	470	45	78	E14		10	A++	15000
---	----------	--------------------------	-----	-----	----	----	-----	--	----	-----	-------



- 4 -
YEARS
GUARANTEE

1

2

3



LED Essence Mini-Ball

d mm l mm Pcs. h



1	43618712	RL-D25 827/C/E14 FIL	2.5	250	45	77	E14		10	A++	15000
2	43619119	RL-D40 827/C/E14 FIL	4.0	470	45	77	E14		10	A++	15000
2	43619257	RL-D40 840/C/E14 FIL	4.0	470	45	77	E14		10	A++	15000
3	43619258	RL-D60 827/C/E14 FIL	6.5	806	45	110	E14		10	A++	15000



1

— 5 —
YEARS
GUARANTEE

W

lm



L70

LED Star Globe

d mm

l mm

Pcs.

h



Glass

1

43519110

RL-G95 100 DIM 827/F/E27

12.0

1521

95

138

E27



10

A++

15000



1

— 5 —
YEARS
GUARANTEE



LED Star Candle

d mm l mm Pcs. h



1	43519229	RL-C40 DIM 827/F/E14	4.5	470	35	97	E14		10	A+	15000
1	43518710	RL-C60 DIM 827/F/E14	6.5	806	35	97	E14		10	A++	15000



1

— 4 —
YEARS
GUARANTEE



LED Essence Candle

d mm l mm Pcs. h



1	43618708	RL-C40 827/F/E14	4.0	470	35	100	E14		10	A++	15000
1	43619555	RL-C40 840/F/E14	4.0	470	35	100	E14		10	A++	15000
1	43619249	RL-C60 827/F/E14	6.5	806	35	97	E14		10	A++	15000

— 5 —
YEARS
GUARANTEE

1



W

Im



L70

LED Star Candle

d mm

l mm

Pcs.

h



Glass

1	43519264	RL-C40 DIM 827/C/E14 FIL	4.5	470	35	97	E14		10	A++	15000
---	----------	--------------------------	-----	-----	----	----	-----	--	----	-----	-------

— 4 —
YEARS
GUARANTEE

1



2



3



4



5



W

Im



L70

LED Essence Candle

d mm

l mm

Pcs.

h



Glass

1	43619252	RL-C25 827/C/E14 FIL	2.5	250	35	100	E14		10	A++	15000
2	43618707	RL-C40 827/C/E14 FIL	4.0	470	35	100	E14		10	A++	15000
3	43619250	RL-CA40 827/C/E14 FIL	4.0	470	35	121	E14		10	A++	15000
4	43619251	RL-CW40 827/C/E14 FIL	4.0	470	35	100	E14		10	A++	15000
5	43619253	RL-C60 827/C/E14 FIL	6.5	806	35	118	E14		10	A++	15000

No-name? That was yesterday.

Brilliant light for the quality-conscious.

Today, almost anyone can sell LED lamps at extremely low prices and with less service. But there are more and more people who don't want to buy these no-name products anymore. Our LED lamp family therefore includes high-quality LED spot lamps such as LED R63, LED PAR16 or LED MR16, which set brilliant highlights with directional light and modern design. For quality-conscious people who appreciate not only brand quality but also personal advice.



**„I deliberately pay
attention to where
and, above all, how
production takes place.“**



**LED
Spots**

LED Spots

Spot lighting for professional applications

The new generation focuses on performance

- Direct replacement of incandescent and halogen reflector lamps
- Extremely energy-saving
- Long service life of up to 40,000 hours
- Efficient high-power LEDs
- New innovative design
- Low heat generation
- Many dimmable

Areas of application

- Shops
- Restaurants
- Hotels
- Bars
- Corridors
- Apartments and private homes



**MADE
INGER
MANY.**

**– 5 –
YEARS
GUARANTEE**

W

lm



L70

LED Star PAR16

d mm

l mm

Pcs.

h



MIG.	1	43519192	RL-PAR16 35 DIM 927/WFL	3.7	230	51	55	GU10		10	A+	25000
MIG.	1	43519193	RL-PAR16 50 DIM 927/WFL	5.5	350	51	55	GU10		10	A+	25000
MIG.	1	43519194	RL-PAR16 50 DIM 930/WFL	5.5	350	51	55	GU10		10	A+	25000
MIG.	1	43519195	RL-PAR16 50 DIM 940/WFL	5.5	350	51	55	GU10		10	A+	25000
	1	43319519	RL-PAR16 80 DIM 827/WFL	8.0	575	51	55	GU10		10	A+	25000
	1	43319518	RL-PAR16 80 DIM 830/WFL	8.0	575	51	55	GU10		10	A+	25000
	1	43519198	RL-PAR16 80 DIM 840/WFL	8.0	575	51	55	GU10		10	A+	25000
	2	43519199	RL-PAR16 80 DIM 827/VWFL*	8.0	575	51	55	GU10		10	A+	25000
	2	43518457	RL-PAR16 80 DIM 830/VWFL*	8.0	575	51	55	GU10		10	A+	25000
	2	43519200	RL-PAR16 80 DIM 840/VWFL*	8.0	575	51	55	GU10		10	A+	25000



**MADE
INGER
MANY.**

**— 4 —
YEARS
GUARANTEE**

1

2

W

lm



L70

LED Essence PAR16

d mm

l mm

Pcs.

h



1	43619201	RL-PAR16 50 827/WFL	4.3	350	51	55	GU10	●	10	A++	15000	MIG.
1	43619205	RL-PAR16 50 830/WFL	4.3	350	51	55	GU10	●	10	A++	15000	MIG.
1	43619206	RL-PAR16 50 840/WFL	4.3	350	51	55	GU10	○	10	A++	15000	MIG.
2	43619208	RL-PAR16 50 827/VWFL*	4.3	350	51	55	GU10	●	10	A+	15000	MIG.
2	43618701	RL-PAR16 50 830/VWFL*	4.3	350	51	55	GU10	●	10	A+	15000	MIG.
2	43619209	RL-PAR16 50 840/VWFL*	4.3	350	51	55	GU10	○	10	A+	15000	MIG.
1	43619210	RL-PAR16 80 827/WFL	6.9	575	51	55	GU10	●	10	A+	15000	MIG.
1	43619212	RL-PAR16 80 830/WFL	6.9	575	51	55	GU10	●	10	A+	15000	MIG.
1	43619214	RL-PAR16 80 840/WFL	6.9	575	51	55	GU10	○	10	A+	15000	MIG.
2	43619211	RL-PAR16 80 827/VWFL*	6.9	575	51	55	GU10	●	10	A+	15000	MIG.
2	43618702	RL-PAR16 80 830/VWFL*	6.9	575	51	55	GU10	●	10	A+	15000	MIG.
2	43619213	RL-PAR16 80 840/VWFL*	6.9	575	51	55	GU10	○	10	A+	15000	MIG.



1

— 4 —
YEARS
GUARANTEE

W

lm



L70

LED Essence MR11

d mm

l mm

Pcs.

h



1	43619248	RL-MR11 20 827/WFL	2.5	184	35	38	GU4		10	A+	15000
1	43619244	RL-MR11 35 827/WFL	4.0	345	35	38	GU4		10	A+	15000



1

— 5 —
YEARS
GUARANTEE

W

lm



L70

LED Star MR16

d mm

l mm

Pcs.

h



1	43519239	RL-MR16 35 DIM 927/WFL	6.3	350	51	53	GU5.3		10	A	40000
1	43519240	RL-MR16 35 DIM 930/WFL	6.3	350	51	53	GU5.3		10	A	40000
1	43518455	RL-MR16 35 DIM 940/WFL	6.3	350	51	53	GU5.3		10	A	40000
1	43519241	RL-MR16 43 DIM 927/WFL	7.8	500	51	53	GU5.3		10	A	40000
1	43519242	RL-MR16 43 DIM 930/WFL	7.8	500	51	53	GU5.3		10	A	40000
1	43518456	RL-MR16 43 DIM 940/WFL	7.8	500	51	53	GU5.3		10	A	40000



**MADE
INGER
MANY.**

**— 4 —
YEARS
GUARANTEE**

W

lm



L70

LED Essence MR16

d mm

l mm

Pcs.

h



Glass

2	43019051	RL-MR16 35 827/WFL	4.6	350	51	46	GU5.3		10	A+	15000	MIG.
2	43519220	RL-MR16 35 830/WFL	4.6	350	51	46	GU5.3		10	A+	15000	MIG.
2	43618599	RL-MR16 35 840/WFL	4.6	350	51	46	GU5.3		10	A+	15000	MIG.
1	43618600	RL-MR16 50 827/WFL	7.2	621	51	53	GU5.3		10	A+	15000	
1	43618601	RL-MR16 50 830/WFL	7.2	621	51	53	GU5.3		10	A+	15000	
1	43618602	RL-MR16 50 840/WFL	7.2	621	51	53	GU5.3		10	A+	15000	



**— 5 —
YEARS
GUARANTEE**

W

lm



L70

LED Star AR111

d mm

l mm

Pcs.

h



1	43319535	RL-AR111 75 DIM 930/FL	15.0	800	111	55	G53		6	A	40000	
1	43319536	RL-AR111 75 DIM 930/WFL*	15.0	800	111	55	G53		6	A	40000	

— 3 —
YEARS
GUARANTEE



1



LED Essence GX53

d mm l mm Pcs. h



1	43618461	RL-GX53 40 827/VWFL	6.1	470	75	31	GX53		10	A+	15000
---	----------	---------------------	-----	-----	----	----	------	--	----	----	-------

— 4 —
YEARS
GUARANTEE



1

2

3



LED Essence R50, R63 & R80

d mm l mm Pcs. h



1	43618820	RL-R50 40 827/WFL	2.6	210	50	85	E14		10	A++	15000
2	43618822	RL-R63 60 827/WFL	4.3	345	63	102	E27		10	A+	15000
3	43618705	RL-R80 100 827/WFL	9.1	670	80	113	E27		10	A+	15000



— 5 —
YEARS
GUARANTEE



LED Star PAR20, PAR30 & PAR38

d mm l mm Pcs. h



1	43518459	RL-PAR20 50 DIM 927/WFL	5.0	345	63	78	E27		6	A+	25000
2	43519121	RL-PAR30 75 DIM 927/WFL	10.0	633	95	91	E27		6	A	25000
3	43519122	RL-PAR38 120 DIM 827/WFL*	12.5	1035	120	132	E27		6	A+	25000



— 4 —
YEARS
GUARANTEE



LED Essence PAR38

d mm l mm Pcs. h



1	43618913	RL-PAR38 120 827/SP	12.5	1035	120	132	E27		6	A+	25000
1	43618818	RL-PAR38 120 827/FL*	12.5	1035	120	132	E27		6	A+	25000


Short service life? That was yesterday.

Durable light for the indestructible.

Experience has shown that products manufactured at very low prices often break down faster than you can say “junk lamp.” Many people are therefore looking for really good alternatives that can be trusted in the long term. This is what Radium’s new product range is all about – for example with high-quality LED tubes such as the LED T5 Tubes, LED T8 Tubes or the round LED T9 Ring as replacements for classic fluorescent lamps. For the indestructible who prefer real brand products.



**„Anyone who is serious
about eco-friendliness
should choose products
that last longer.“**



**LED
Tubes**

The type of luminaire is essential.

The right LED tube for every application.

When replacing fluorescent lamps with the latest Radium LED technology, the choice of the right LED tube depends on the type of luminaire. Basically, there are three circuit options:


- With direct wiring, the LED tube is operated directly on mains voltage. If the existing luminaire is not designed for this type of operation, the luminaire must be converted. We always recommend to use the supplied LED starter and to mark the luminaire clearly (only for LED tubes).
- For luminaires with conventional control gear (CCG), the fluorescent tube is replaced 1:1 by an LED tube. In addition, the starter is replaced by the supplied LED starter. We recommend removing the compensation capacitor.
- Our HF or UN versions are suitable for luminaires with electronic control gear (ECG). The tubes are replaced 1:1, but compatibility must be checked against the compatibility list.



Which operating mode is being used?



Direct wiring (230V).



Which output do you need?

LED Essence T9 Ring EM

Up to 2000lm

Electromagnetic

Page 32

LED Star Tube T5 HE UN

Up to 2800lm

High Efficiency
Universal
Page 29

LED Star Tube T8 UN

Up to 3100lm

Universal

Page 30

LED Star Tube T8 EM

Up to 3100lm

Electromagnetic

Page 31

LED Star Tube T8 HO UN

Up to 3700lm

High Output
Universal
Page 30

205mm

RL-T9 C22 840/G10q EM ☐

RL-T9 C22 865/G10q EM ☒

298 mm

RL-T9 C32 840/G10q EM ☐

RL-T9 C32 865/G10q EM ☒

LED Essence Tube T8 EM

Up to 2000lm

Electromagnetic

Page 32

600mm

RL-T8 18 830/G13 EM ☐

RL-T8 18 840/G13 EM ☐

RL-T8 18 865/G13 EM ☒

1200mm

RL-T8 36 830/G13 EM ☐

RL-T8 36 840/G13 EM ☐

RL-T8 36 865/G13 EM ☒

1500mm

RL-T8 58 830/G13 EM ☐

RL-T8 58 840/G13 EM ☐

RL-T8 58 865/G13 EM ☒

549mm

RL-T5 14 HE 830/G5 UN ☐

RL-T5 14 HE 840/G5 UN ☐

RL-T5 14 HE 865/G5 UN ☒

849mm

RL-T5 21 HE 830/G5 UN ☐

RL-T5 21 HE 840/G5 UN ☐

RL-T5 21 HE 865/G5 UN ☒

1149mm

RL-T5 28 HE 830/G5 UN ☐

RL-T5 28 HE 840/G5 UN ☐

RL-T5 28 HE 865/G5 UN ☒

1449mm

RL-T5 35 HE 830/G5 UN ☐

RL-T5 35 HE 840/G5 UN ☐

RL-T5 35 HE 865/G5 UN ☒

600mm

RL-T8 18 S 830/G13 UN ☐

RL-T8 18 S 840/G13 UN ☐

RL-T8 18 S 865/G13 UN ☒

1200mm

RL-T8 36 S 830/G13 UN ☐

RL-T8 36 S 840/G13 UN ☐

RL-T8 36 S 865/G13 UN ☒

1500mm

RL-T8 58 S 830/G13 UN ☐

RL-T8 58 S 840/G13 UN ☐

RL-T8 58 S 865/G13 UN ☒

600mm

RL-T8 18 S 840/G13 EM ☐

RL-T8 18 S 865/G13 EM ☒

900mm

RL-T8 30 S 840/G13 EM ☐

RL-T8 30 S 865/G13 EM ☒

1200mm

RL-T8 36 S 840/G13 EM ☐

RL-T8 36 S 865/G13 EM ☒

1500mm

RL-T8 58 S 840/G13 EM ☐

RL-T8 58 S 865/G13 EM ☒

LED Star Tube T8 HO EM

Up to 3700lm

High Output
Electromagnetic
Page 31

1200mm

RL-T8 36 HO 840/G13 EM ☐

RL-T8 36 HO 865/G13 EM ☒

1500mm

RL-T8 58 HO 840/G13 EM ☐

RL-T8 58 HO 865/G13 EM ☒

1200mm

RL-T8 36 HO 840/G13 UN ☐

RL-T8 36 HO 865/G13 UN ☒

1500mm

RL-T8 58 HO 840/G13 UN ☐

RL-T8 58 HO 865/G13 UN ☒

LED Star Tube T5 HO UN

Up to 5600lm

High Output
Universal
Page 28

1149mm

RL-T5 54 HO 830/G5 UN ☐

RL-T5 54 HO 840/G5 UN ☐

RL-T5 54 HO 865/G5 UN ☒

1449mm

RL-T5 49 HO 830/G5 UN ☐

RL-T5 49 HO 840/G5 UN ☐

RL-T5 49 HO 865/G5 UN ☒

1449mm

RL-T5 80 HO 830/G5 UN ☐

RL-T5 80 HO 840/G5 UN ☐

RL-T5 80 HO 865/G5 UN ☒

Which operating mode is being used?



CCG operation.

Lamp




+

Starter



+

Conventional control gear



Which output do you need?

**LED Essence
T9 Ring EM**

Up to 2000lm
Electromagnetic
Page 32

**LED Essence
Tube T8 EM**

Up to 2000lm
Electromagnetic
Page 32

**LED Star
Tube T8 EM**

Up to 3100lm
Electromagnetic
Page 31

**LED Star
Tube T8 UN**

Up to 3100lm
Universal
Page 30

**LED Star
Tube T8 HO EM**

Up to 3700lm
High Output
Electromagnetic
Page 31

205mm

RL-T9 C22 840/G10q EM ☐

RL-T9 C22 865/G10q EM ☐

298mm

RL-T9 C32 840/G10q EM ☐

RL-T9 C32 865/G10q EM ☐

600mm

RL-T8 18 830/G13 EM ☐

RL-T8 18 840/G13 EM ☐

RL-T8 18 865/G13 EM ☐

1200mm

RL-T8 36 830/G13 EM ☐

RL-T8 36 840/G13 EM ☐

RL-T8 36 865/G13 EM ☐

1500mm

RL-T8 58 830/G13 EM ☐

RL-T8 58 840/G13 EM ☐

RL-T8 58 865/G13 EM ☐

600mm

RL-T8 18 S 840/G13 EM ☐

RL-T8 18 S 865/G13 EM ☐

900mm

RL-T8 30 S 840/G13 EM ☐

RL-T8 30 S 865/G13 EM ☐

1200mm

RL-T8 36 S 840/G13 EM ☐

RL-T8 36 S 865/G13 EM ☐

1500mm

RL-T8 58 S 840/G13 EM ☐

RL-T8 58 S 865/G13 EM ☐

600mm

RL-T8 18 S 830/G13 UN ☐

RL-T8 18 S 840/G13 UN ☐

RL-T8 18 S 865/G13 UN ☐

1200mm

RL-T8 36 S 830/G13 UN ☐

RL-T8 36 S 840/G13 UN ☐

RL-T8 36 S 865/G13 UN ☐

1500mm

RL-T8 58 S 830/G13 UN ☐

RL-T8 58 S 840/G13 UN ☐

RL-T8 58 S 865/G13 UN ☐

1200mm

RL-T8 36 HO 840/G13 EM ☐

RL-T8 36 HO 865/G13 EM ☐

1500mm

RL-T8 58 HO 840/G13 EM ☐

RL-T8 58 HO 865/G13 EM ☐

**LED Star
Tube T8 HO UN**

Up to 3700lm

High Output
Universal
Page 30

1200mm

RL-T8 36 HO 840/G13 UN ☐

RL-T8 36 HO 865/G13 UN ☐

1500mm

RL-T8 58 HO 840/G13 UN ☐

RL-T8 58 HO 865/G13 UN ☐

Which operating mode is being used?

ECG


ECG operation.

Lamp



+

Electronic control gear



Which output do you need?

LED Star Tube T5 HE UN

Up to 2800lm

High Efficiency
Universal
Page 29

LED Star Tube T8 UN

Up to 3100lm

Universal
Page 30

LED Star Tube T8 HO UN

Up to 3700lm

High Output
Universal
Page 30

LED Star Tube T5 HO UN

Up to 5600lm

High Output
Universal
Page 28

549mm

RL-T5 14 HE 830/G5 UN ☐

RL-T5 14 HE 840/G5 UN ☐

RL-T5 14 HE 865/G5 UN ☐

600mm

RL-T8 18 S 830/G13 UN ☐

RL-T8 18 S 840/G13 UN ☐

RL-T8 18 S 865/G13 UN ☐

1200mm

RL-T8 36 HO 840/G13 UN ☐

RL-T8 36 HO 865/G13 UN ☐

1149mm

RL-T5 54 HO 830/G5 UN ☐

RL-T5 54 HO 840/G5 UN ☐

RL-T5 54 HO 865/G5 UN ☐

849mm

RL-T5 21 HE 830/G5 UN ☐

RL-T5 21 HE 840/G5 UN ☐

RL-T5 21 HE 865/G5 UN ☐

1200mm

RL-T8 36 S 830/G13 UN ☐

RL-T8 36 S 840/G13 UN ☐

RL-T8 36 S 865/G13 UN ☐

1500mm

RL-T8 58 HO 840/G13 UN ☐

RL-T8 58 HO 865/G13 UN ☐

1449mm

RL-T5 49 HO 830/G5 UN ☐

RL-T5 49 HO 840/G5 UN ☐

RL-T5 49 HO 865/G5 UN ☐

RL-T5 80 HO 830/G5 UN ☐

RL-T5 80 HO 840/G5 UN ☐

RL-T5 80 HO 865/G5 UN ☐

1149mm

RL-T5 28 HE 830/G5 UN ☐

RL-T5 28 HE 840/G5 UN ☐

RL-T5 28 HE 865/G5 UN ☐

1500mm

RL-T8 58 S 830/G13 UN ☐

RL-T8 58 S 840/G13 UN ☐

RL-T8 58 S 865/G13 UN ☐

1449mm

RL-T5 35 HE 830/G5 UN ☐

RL-T5 35 HE 840/G5 UN ☐

RL-T5 35 HE 865/G5 UN ☐

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility

LED Tubes

Energy-saving alternatives to fluorescent tubes

High-quality lighting for a wide range of tasks

- Classic design with glass bulb
- Direct replacement of traditional T8 and T5 fluorescent lamps (ECG or CCG operation)
- Homogeneous light distribution and high luminous flux even at cold ambient temperatures
- Extremely energy-saving: up to 60%
- Easy handling, no modification of the luminaire
- Fast and flicker-free start
- Wide beam angle
- Rotatable end caps (for Star Tube)

Areas of application

- Industrial lighting
- Parking garages
- Paths and corridors
- Maintenance rooms
- Indirect lighting
- Backlighting

– 5 –
YEARS
GUARANTEE



1



LED Star Tube T5 HO UN

d mm

l mm

Pcs.

h



1	43518502	RL-T5 49 HO 830/G5 UN	26.0	3600	21	1449	G5	●	10	A++	60000
1	43519548	RL-T5 49 HO 840/G5 UN	26.0	4000	21	1449	G5	○	10	A++	60000
1	43518504	RL-T5 49 HO 865/G5 UN	26.0	4000	21	1449	G5	●	10	A++	60000
1	43518499	RL-T5 54 HO 830/G5 UN	26.0	3600	21	1149	G5	●	10	A++	60000
1	43519549	RL-T5 54 HO 840/G5 UN	26.0	4000	21	1149	G5	○	10	A++	60000
1	43518501	RL-T5 54 HO 865/G5 UN	26.0	4000	21	1149	G5	●	10	A++	60000
1	43518480	RL-T5 80 HO 830/G5 UN	37.0	5050	21	1449	G5	●	10	A++	60000
1	43519550	RL-T5 80 HO 840/G5 UN	37.0	5600	21	1449	G5	○	10	A++	60000
1	43518482	RL-T5 80 HO 865/G5 UN	37.0	5600	21	1449	G5	●	10	A++	60000

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility



**— 5 —
YEARS
GUARANTEE**



1



LED Star Tube T5 HE UN

d mm

l mm

Pcs.

h



1	43518516	RL-T5 14 HE 830/G5 UN	7.0	900	21	549	G5	●	10	A++	60000
1	43519545	RL-T5 14 HE 840/G5 UN	7.0	1000	21	549	G5	○	10	A++	60000
1	43518520	RL-T5 14 HE 865/G5 UN	7.0	1000	21	549	G5	●	10	A++	60000
1	43518513	RL-T5 21 HE 830/G5 UN	10.0	1350	21	849	G5	●	10	A++	60000
1	43518514	RL-T5 21 HE 840/G5 UN	10.0	1500	21	849	G5	○	10	A++	60000
1	43518515	RL-T5 21 HE 865/G5 UN	10.0	1500	21	849	G5	●	10	A++	60000
1	43518510	RL-T5 28 HE 830/G5 UN	17.0	2350	21	1149	G5	●	10	A++	60000
1	43519546	RL-T5 28 HE 840/G5 UN	17.0	2600	21	1149	G5	○	10	A++	60000
1	43518512	RL-T5 28 HE 865/G5 UN	17.0	2600	21	1149	G5	●	10	A++	60000
1	43518505	RL-T5 35 HE 830/G5 UN	18.0	2550	21	1449	G5	●	10	A++	60000
1	43519547	RL-T5 35 HE 840/G5 UN	18.0	2800	21	1449	G5	○	10	A++	60000
1	43518509	RL-T5 35 HE 865/G5 UN	18.0	2800	21	1449	G5	●	10	A++	60000

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility

**— 5 —
YEARS
GUARANTEE**



1



LED Star Tube T8 HO UN

d mm l mm Pcs. h



1	43519223	RL-T8 36 HO 840/G13 UN	15.0	2400	28	1200	G13	○	10	A++	60000
1	43519224	RL-T8 36 HO 865/G13 UN	15.0	2400	28	1200	G13	●	10	A++	60000
1	43519225	RL-T8 58 HO 840/G13 UN	23.0	3700	28	1500	G13	○	10	A++	60000
1	43519226	RL-T8 58 HO 865/G13 UN	23.0	3700	28	1500	G13	●	10	A++	60000

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility

**— 5 —
YEARS
GUARANTEE**



1



LED Star Tube T8 UN

d mm l mm Pcs. h



1	43518415	RL-T8 18 S 830/G13 UN	7.5	1000	28	600	G13	●	10	A++	50000
1	43519542	RL-T8 18 S 840/G13 UN	7.5	1100	28	600	G13	○	10	A++	50000
1	43518419	RL-T8 18 S 865/G13 UN	7.5	1100	28	600	G13	●	10	A++	50000
1	43518420	RL-T8 36 S 830/G13 UN	14.0	1900	28	1200	G13	●	10	A++	50000
1	43519543	RL-T8 36 S 840/G13 UN	14.0	2100	28	1200	G13	○	10	A++	50000
1	43518422	RL-T8 36 S 865/G13 UN	14.0	2100	28	1200	G13	●	10	A++	50000
1	43518438	RL-T8 58 S 830/G13 UN	20.0	2800	28	1500	G13	●	10	A++	50000
1	43519544	RL-T8 58 S 840/G13 UN	20.0	3100	28	1500	G13	○	10	A++	50000
1	43518441	RL-T8 58 S 865/G13 UN	20.0	3100	28	1500	G13	●	10	A++	50000

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility

— 5 —
YEARS
GUARANTEE



1



LED Star Tube T8 HO EM

d mm l mm Pcs. h



1	43519215	RL-T8 36 HO 840/G13 EM	15.1	2500	26.7	1200	G13	○	10	A++	60000
1	43519216	RL-T8 36 HO 865/G13 EM	15.1	2500	26.7	1200	G13	●	10	A++	60000
1	43519217	RL-T8 58 HO 840/G13 EM	22.4	3700	26.7	1500	G13	○	10	A++	60000
1	43519218	RL-T8 58 HO 865/G13 EM	22.4	3700	26.7	1500	G13	●	10	A++	60000

— 5 —
YEARS
GUARANTEE



1



LED Star Tube T8 EM

d mm l mm Pcs. h



1	43518307	RL-T8 18 S 840/G13 EM	7.3	1100	26.7	600	G13	○	10	A++	50000
1	43518308	RL-T8 18 S 865/G13 EM	7.3	1100	26.7	600	G13	●	10	A++	50000
1	43518309	RL-T8 30 S 840/G13 EM	11.3	1700	26.7	900	G13	○	10	A++	50000
1	43518320	RL-T8 30 S 865/G13 EM	11.3	1700	26.7	900	G13	●	10	A++	50000
1	43518321	RL-T8 36 S 840/G13 EM	14.0	2100	26.7	1200	G13	○	10	A++	50000
1	43518322	RL-T8 36 S 865/G13 EM	14.0	2100	26.7	1200	G13	●	10	A++	50000
1	43518350	RL-T8 58 S 840/G13 EM	20.6	3100	26.7	1500	G13	○	10	A++	50000
1	43518351	RL-T8 58 S 865/G13 EM	20.6	3100	26.7	1500	G13	●	10	A++	50000

— 3 —
YEARS
GUARANTEE



1



LED Essence Tube T8 EM

d mm l mm Pcs. h



1	43618521	RL-T8 18 830/G13 EM	7.6	720	26.7	600	G13		10	A+	30000
1	43618522	RL-T8 18 840/G13 EM	7.6	800	26.7	600	G13		10	A+	30000
1	43618523	RL-T8 18 865/G13 EM	7.6	800	26.7	600	G13		10	A+	30000
1	43618524	RL-T8 36 830/G13 EM	16.2	1530	26.7	1200	G13		10	A+	30000
1	43618525	RL-T8 36 840/G13 EM	16.2	1700	26.7	1200	G13		10	A+	30000
1	43618526	RL-T8 36 865/G13 EM	16.2	1700	26.7	1200	G13		10	A+	30000
1	43618527	RL-T8 58 830/G13 EM	19.1	1800	26.7	1500	G13		10	A+	30000
1	43618530	RL-T8 58 840/G13 EM	19.1	2000	26.7	1500	G13		10	A+	30000
1	43618531	RL-T8 58 865/G13 EM	19.1	2000	26.7	1500	G13		10	A+	30000

— 3 —
YEARS
GUARANTEE



1

2



LED Essence T9 Ring EM

d mm l mm Pcs. h



1	43218810	RL-T9 C22 840/G10q EM	12.0	1200	205	—	G10q		10	A+	30000
1	43218811	RL-T9 C22 865/G10q EM	12.0	1200	205	—	G10q		10	A+	30000
2	43218812	RL-T9 C32 840/G10q EM	20.0	2000	298	—	G10q		10	A+	30000
2	43218813	RL-T9 C32 865/G10q EM	20.0	2000	298	—	G10q		10	A+	30000



Cheap rubbish? That was yesterday.

High-quality light for valuable people.

Today, LEDs are increasingly being installed in luminaires that, in the event of a defect, can only be disposed of as a whole. However, more and more people want to be able to replace lamps and thus contribute to more environmental protection. High-quality LED Special Lamps from Radium support this trend – e.g. with LED HRL, LED R7s or LED PIN as replacements for halogen, compact fluorescent or mercury vapor lamps. For all those who are already thinking about future generations.



**„Our principle is to replace
lamps instead of throwing
away entire luminaires.“**



**LED
Special
Lamps**

1

2

3

4

MADE
INGER
MANY.- 3 -
YEARS
GUARANTEE

W

lm



L70

RaLEDina Essence

d mm

l mm

Pcs.

h



Glass

1	42614827	RL-RAL1 35 827/0	3.5	260	29	300	S14D		10	A+	15000	MIG.
2	42614831	RL-RAL1 60 827/0	6.0	470	29	500	S14D		10	A+	15000	MIG.
3	42614825	RL-RAL2 35 827/0	3.5	260	29	300	S14S		10	A+	15000	MIG.
4	42614829	RL-RAL2 60 827/0	6.0	470	29	500	S14S		10	A+	15000	MIG.

1

2

COLOR



RaLEDina lamp holder

l mm

w mm

h mm

1	ZLFA0945	RAL1/Holder/S14D	grey	82	46	34	S14D	
2	ZLFA1530	RAL2/Holder/S14S	white	67	36	36	S14S	



**- 5 -
YEARS
GUARANTEE**

W

lm



L70

LED Essence HRL EM

d mm

l mm

Pcs.

h



1	43618301	RL-HRL50 840/E27	16.0	2000	75	153	E27	○	6	A++	50000
2	43618302	RL-HRL80 840/E27	30.0	4000	75	170	E27	○	6	A++	50000
3	43618303	RL-HRL125 840/E27	46.0	6000	80	195	E27	○	6	A++	50000
3	43618304	RL-HRL125 840/E40	46.0	6000	80	204	E40	○	6	A++	50000
4	43618306	RL-HRL250 840/E40	95.0	13000	110	270	E40	○	6	A++	50000





— 3 —
YEARS
GUARANTEE



LED Essence DUO G24d EM

d mm l mm Pcs. h



1	43218902	RL-DU013 840/G24d-1 EM	5.0	600	35	148	G24d-1	○	10	A++	30000
1	43018021	RL-DU018 840/G24d-2 EM	7.0	700	35	148	G24d-2	○	10	A+	30000
2	43018022	RL-DU026 840/G24d-3 EM	10.0	1000	35	171	G24d-3	○	10	A+	30000



— 3 —
YEARS
GUARANTEE



LED Essence Long HF

d mm l mm Pcs. h



1	43218815	RL-LONG18 840/2G11 HF	7.0	1000	38	223	2G11	○	10	A++	30000
2	43218816	RL-LONG36 840/2G11 HF	18.0	2300	38	407	2G11	○	10	A++	30000

Operate only on approved ECGs according to Radium compatibility list www.radium.de/compatibility



**— 5 —
YEARS
GUARANTEE**



LED Star R7s

d mm l mm Pcs. h



1	43518617	RL-TSK100 DIM 827/R7S*	11.5	1521	29	78	R7s		20	A++	15000
2	43518616	RL-TS125 DIM 827/R7S	15.0	2000	28	118	R7s		20	A++	25000



**— 4 —
YEARS
GUARANTEE**



LED Essence R7s

d mm l mm Pcs. h



1	43619246	RL-TSK 60 827/R7S	7.0	806	29	78	R7s		20	A++	15000
1	43619247	RL-TSK 75 827/R7S	8.0	1055	29	78	R7s		20	A++	15000
2	43619243	RL-TS 100 827/R7S	12.5	1521	29	118	R7s		20	A++	15000
3	43619245	RL-TS 150 827/R7S*	17.5	2452	28	118	R7s		20	A++	15000

— 5 —
YEARS
GUARANTEE



1



LED Star PIN

d mm l mm Pcs. h



1	43518677	RL-PIN32 DIM 827/C/G9	3.5	350	20	58	G9		20	A++	25000
---	----------	-----------------------	-----	-----	----	----	----	--	----	-----	-------

— 4 —
YEARS
GUARANTEE



1

2

3



LED Essence PIN

d mm l mm Pcs. h



1	43618557	RL-PIN28 827/C/G4	2.4	300	13	44	G4		20	A++	15000
2	43618552	RL-PIN28 827/C/GY6.35	2.4	300	13	57	GY6.35		20	A++	15000
3	43219457	RL-PIN40 827/C/G9	3.8	470	20	58	G9		20	A++	15000



— 3 —
YEARS
GUARANTEE

1



LED Essence T26

d mm l mm Pcs. h



1	43619109	RL-T26 25 827/C/E14	2.8	250	26	63	E14		20	A++	10000
---	----------	---------------------	-----	-----	----	----	-----	--	----	-----	-------



— 4 —
YEARS
GUARANTEE

1



LED Essence T26

d mm l mm Pcs. h



1	43618614	RL-T26 40 827/C/E14	4.0	470	25	80	E14		20	A++	15000
---	----------	---------------------	-----	-----	----	----	-----	--	----	-----	-------




Save more energy with Radium.

LED's Save Calculator.

With so many LED products around, do you still know what's what anymore? If not, don't worry. With the LED's Save Calculator, you will find the right LED replacement product in no time at all. And so that you can see whether the exchange is really worth it, you will get a result with energy costs and payback time. Let your savings potential surprise you today.

www.radium.de/en/leds-save



Important facts at a glance.

Technical information.

General information about LEDs

All technical parameters apply to the whole lamp. Due to the complex manufacturing process of light-emitting diodes, the values given for the technical LED parameters are purely statistical and do not necessarily correspond to the actual technical parameters of each individual product, which may differ from the typical value.

Dimming behavior

Due to different technological concepts, the dimming behavior of lamps with integrated control gears differs from the behavior of conventional incandescent or halogen lamps and may therefore be restricted in certain cases. Under unfavorable conditions (many possible influencing factors), the electronic components contained may develop noise. For more information about lamp dimmer compatibility, please go to www.radium.de/en/dim.



TIP: You can also control our lamps with your smartphone. Find more information at www.radium.de/en/smart-blue/ted



What's behind all this?

Explanation of pictograms.



Direct wiring

Suitable for operation on mains voltage. If the existing luminaire is not designed for this operating mode, the luminaire must be modified. In any case, we recommend to use the supplied LED starter and to clearly mark the lamp.



CCG

Suitable for operation with conventional control gear (CCG) as well as directly with mains voltage. For operation with a CCG, the existing starter must be replaced with the LED starter included in the delivery. We recommend removing the compensation capacitor.



ECG

Suitable for operation with an electronic control gear (ECG). Compatibility must be checked in advance using the compatibility list.
www.radium.de/compatibility



Glass

True to original design with high-quality glass bulb



Shatter resistance

Shatter resistance according to IEC 61549 AMD 2:2010 -810-1 4.4.1



Guarantee

Radium LED lamps are known for high-quality engineering, professional thermal management, the use of high-quality components and the application of systematic quality assurance measures. Radium provides guarantees of up to 5 years on LED lamps which are operated in accordance with the product and application guidelines specified by Radium, e.g. data sheets, application notes or compatibility lists. www.radium.de/guarantee



Made in Germany

Many products within the Radium LED lamp portfolio are manufactured directly in Germany and therefore stand for particularly good quality.



Star

Optimum function for professional use. All Star models offer a longer service life and very good efficiency.



Essence

All Essence models offer pure functionality at the best price



Power consumption (watts)



Luminous flux (lumens)



Dimensions in millimeters (mm)



Base



Color temperature
● 2700/3000 K (warm white)
○ ~ 4000 K (neutral white)
● ~ 6500 K (cool white)



Shipping unit in pieces (pcs.)



Energy label



L70B50 Service life



Color



Ingress protection rating (IP)



Beam angle



Dimmable. For compatibility information, see page 45 (Dimming behavior).

Radium Lampenwerk GmbH

Dr.-Eugen-Kersting-Str. 6
51688 Wipperfürth
Germany

Phone +49 (0) 2267 811
Fax +49 (0) 2267 81353

radium@radium.de
www.radium.de